

TECHNICAL CHARACTERISTICS	RCS 8	RCS 10	RCS 12
Wheels	8	10	12
Wheel diameter	55" (140 cm)	55" (140 cm)	55" (140 cm)
Tractor horsepower	20 Hp (15 kW)	20 Hp (15 kW)	25 Hp (19 kW)
Hitch	Clevis	Clevis	Clevis
Maximum raking width	19'8" (590 cm)	22' (660 cm)	24'4" (730 cm)
Windrow width	3' - 5' (90 - 150 cm)	3' - 6' (90 - 180 cm)	3' - 6' (90 - 180 cm)
Weight	1,038 lb. (472 kg)	1,174 lb. (534 kg)	1,386 lb. (629 kg)
Transport width	10' (300 cm)	10'4" (320 cm)	11'4" (340 cm)
Appropriate working speed	14 mph (22 kmh)	14 mph (22 kmh)	14 mph (22 kmh)
Minimum hydraulic requirements	1,000 psi (68.95 bar)	1,000 psi (68.95 bar)	1,000 psi (68.95 bar)
Hitch jack	Standard	Standard	Standard
Tires	185/65 - 14	185/65 - 14	185/65 - 14


OPTIONAL

Center kicker wheel	●	●	●
Kit blocking one rake	●	●	●
Wind shields	●	●	●

88261001



TONUTTI reserves the right to make changes or add improvements at any time without notice. The information contained herein is general in nature and is not intended for specific application purposes.



Patent number
5,313,772 - 5,231,829
Other patents pending

Tonutti Italy
Via Gino Tonutti 3 - 33047
Remanzacco (UD) Italy
Tel. + 39 0432 667015
Fax + 39 0432 668282
info@tonutti.it
www.tonutti.it

Tonutti U.S.A.
S&T Distributing, Inc.
1909 Thomas Road
Memphis, TN 38134
Phone (901) 385 8841
Fax (901) 385 8288
info@tonuttiusa.com
www.tonuttiusa.com

Tonutti Russia
G.M.T. Limited
3 Tekhnicheskaya Street
Perm, 614070 Russia
Phone 007 (3422) 909096
Fax 007 (3422) 909096
gmtita@perm.ru





TONUTTI RCS-CARTED RAKES are available in 8-, 10-, and 12- wheel models. These high quality and durable rakes are easily adaptable to your crop conditions. Their wide cart and low center of gravity ensure a stable and secure operation even on inclines and in hilly areas.

Two rake wheels are independently mounted together on one pivoting arm to follow ground contours. Finger wheels with specially shaped tines made of flexible steel gently rake

the crop to produce a consistent and fluffy windrow suitable to form an even and compact bale.

The RCS rakes come with one single acting hydraulic cylinder to raise the rakes on-the-go right from the tractor cab. When needed, either side can be locked in transport position to rake only with one side. (optional kit)

The RCS carted rakes can be set-up and fine-tuned to your crop conditions like almost no other rake on the market: Additional turnbuckles allow a perfect fine-tuning of the windrow width.

By regulating the turnbuckles differently on each side, the windrow can be off-set either to the left or to the right. In this way two windrows can be easily raked together.

A shock-absorbing spring under each pivoting head controls the right ground pressure when working in rough or uneven terrain.

1. A shock-absorber to provide smooth performance even on rough and uneven terrain.
2. Cylinder stop mechanism to ensure safety on the road.
3. Turnbuckles on each side to easily fine tune the windrow width in a few seconds on the field. Turnbuckles can be adjusted to off-set windrows to one or the other side, which makes it easy to rake two windrows together.
4. A turnbuckle is positioned on each side of the rake and allows to perfectly set the rake wheel pressure on the ground.
5. Two rake wheels are independently mounted together on one pivoting arm to follow ground contours.
6. One single acting hydraulic cylinder to raise rake side frames on-the-go from the tractor cab.

OPTIONS

7. Optional: Center Kicker Wheel to turn the center of the windrow by half turn to fluff up crop, increase dry-down and to prevent the need to run your baler pickup in the ground.

